

Accredited entity according to ČSN EN ISO/IEC 17025:2018:

VF, a.s.
CAB number 2336, VF Calibration Laboratory
Svitavská 588, 679 21, Černá Hora

CMC for the field of measured quantity: Quantities of atomic and nuclear physics

Ord. number ¹	Calibrated quantity / Subject of calibration	Nominal range				Parameter(s) of the measurand	Lowest stated expanded measurement uncertainty ²	Calibration principle	Calibration procedure identification ³	Work-place
		min.	unit	max.	unit					
1	Kerma in air (Ka) /Meters of ionizing radiation dosimetry quantities	200·10 ⁻⁹	Gy	to	110·10 ⁻⁸	Gy	3.9 %	Measurement on the OG-8 irradiator	VF 1Q-3P2-0101	
		110·10 ⁻⁸	Gy	to	300·10 ⁻⁷	Gy	2.2 %			
	Kerma rate in air (p Ka) / Meters of ionizing radiation dosimetry quantities	300·10 ⁻⁹	Gy·h ⁻¹	to	120·10 ⁻⁷	Gy·h ⁻¹	Position OG-8 ⁴	4	2.2 %	VF 1Q-3P2-0101
							5	3.9 %		
							7	4.9 %		
		120·10 ⁻⁷	Gy·h ⁻¹	to	710·10 ⁻⁷	Gy·h ⁻¹	4	2.2 %		
							5	3.9 %		
		710·10 ⁻⁷	Gy·h ⁻¹	to	150·10 ⁻⁵	Gy·h ⁻¹	1	2.5 %		
							4	2.2 %		
		150·10 ⁻⁵	Gy·h ⁻¹	to	290·10 ⁻⁴	Gy·h ⁻¹	1	2.5 %		
							3	2.2 %		
		290·10 ⁻⁴	Gy·h ⁻¹	to	970·10 ⁻³	Gy·h ⁻¹	2	2.2 %		
							3	2.2 %		
		970·10 ⁻³	Gy·h ⁻¹	to	9	Gy·h ⁻¹	2	2.2 %		

**The Appendix is an integral part of
Certificate of Accreditation No. 516/2023 of 02/10/2023**

Accredited entity according to ČSN EN ISO/IEC 17025:2018:

VF, a.s.
CAB number 2336, VF Calibration Laboratory
Svitavská 588, 679 21, Černá Hora

Ord. number ¹	Calibrated quantity / Subject of calibration	Nominal range				Parameter(s) of the measurand	Lowest stated expanded measurement uncertainty ²	Calibration principle	Calibration procedure identification ³	Work-place	
		min.	unit	max.	unit						
	Spatial dose equivalent ($H^*(10)$) / Meters of ionizing radiation dosimetry quantities	$241 \cdot 10^{-9}$ Sv	to	$132 \cdot 10^{-8}$ Sv			3.9 %	Measurement on the OG-8 irradiator	VF 1Q-3P2-0101		
		$132 \cdot 10^{-8}$ Sv	to	$361 \cdot 10^{-7}$ Sv			2.2 %				
		$361 \cdot 10^{-7}$ Sv	to	$144 \cdot 10^{-5}$ Sv			2.5 %				
		$144 \cdot 10^{-5}$ Sv	to	360 Sv			2.2 %				
	Spatial dose equivalent rate ($pH^*(10)$) / Meters of ionizing radiation dosimetry quantities	$361 \cdot 10^{-9}$ Sv·h ⁻¹	to	$144 \cdot 10^{-7}$ Sv·h ⁻¹		Position OG-8 ⁴	4	2.2 %	Measurement on the OG-8 irradiator	VF 1Q-3P2-0101	
							5	3.9 %			
							7	4.9 %			
		$144 \cdot 10^{-7}$ Sv·h ⁻¹	to	$855 \cdot 10^{-7}$ Sv·h ⁻¹			4	2.2 %			
							5	3.9 %			
		$855 \cdot 10^{-7}$ Sv·h ⁻¹	to	$181 \cdot 10^{-5}$ Sv·h ⁻¹			1	2.5 %			
							4	2.2 %			
		$181 \cdot 10^{-5}$ Sv·h ⁻¹	to	$349 \cdot 10^{-4}$ Sv·h ⁻¹			1	2.5 %			
							3	2.2 %			
		$349 \cdot 10^{-4}$ Sv·h ⁻¹	to	$117 \cdot 10^{-2}$ Sv·h ⁻¹			2	2.2 %			
							3	2.2 %			
		$117 \cdot 10^{-2}$ Sv·h ⁻¹	to	10.8 Sv·h ⁻¹			2	2.2 %			
	Personal dose equivalent ($Hp(10)$) / Meters of ionizing radiation dosimetry quantities	$243 \cdot 10^{-9}$ Sv	to	$134 \cdot 10^{-8}$ Sv			3.9 %	Measurement on the OG-8 irradiator	VF 1Q-3P2-0101		
		$134 \cdot 10^{-8}$ Sv	to	$365 \cdot 10^{-7}$ Sv			2.2 %				
		$365 \cdot 10^{-7}$ Sv	to	$146 \cdot 10^{-5}$ Sv			2.5 %				
		$146 \cdot 10^{-5}$ Sv	to	365 Sv			2.2 %				

Accredited entity according to ČSN EN ISO/IEC 17025:2018:

VF, a.s.
CAB number 2336, VF Calibration Laboratory
Svitavská 588, 679 21, Černá Hora

Ord. number ¹	Calibrated quantity / Subject of calibration	Nominal range				Parameter(s) of the measurand	Lowest stated expanded measurement uncertainty ²	Calibration principle	Calibration procedure identification ³	Work-place
		min.	unit	max.	unit					
Personal dose equivalent rate (p Hp(10)) / Meters of ionizing radiation dosimetry quantities		365·10 ⁻⁹ Sv·h ⁻¹	to	146·10 ⁻⁷ Sv·h ⁻¹		Position OG-8 ⁴	4	2.2 %	Measurement on the OG-8 irradiator	VF 1Q-3P2-0101
							5	3.9 %		
							7	4.9 %		
		146·10 ⁻⁷ Sv·h ⁻¹	to	863·10 ⁻⁷ Sv·h ⁻¹			4	2.2 %		
							5	3.9 %		
		863·10 ⁻⁷ Sv·h ⁻¹	to	182·10 ⁻⁵ Sv·h ⁻¹			1	2.5 %		
							4	2.2 %		
Photon dose equivalent (Hx) / Meters of ionizing radiation dosimetry quantities		182·10 ⁻⁵ Sv·h ⁻¹	to	352·10 ⁻⁴ Sv·h ⁻¹			1	2.5 %	Measurement on the OG-8 irradiator	VF 1Q-3P2-0101
							3	2.2 %		
		352·10 ⁻⁴ Sv·h ⁻¹	to	118·10 ⁻² Sv·h ⁻¹			2	2.2 %		
							3	2.2 %		
Photon dose equivalent rate (p Hx) / Meters of ionizing radiation dosimetry quantities		118·10 ⁻² Sv·h ⁻¹	to	10.8 Sv·h ⁻¹			2	2.2 %	Measurement on the OG-8 irradiator	VF 1Q-3P2-0101
		228·10 ⁻⁹ Sv	to	126·10 ⁻⁸ Sv				3.9 %		
		126·10 ⁻⁸ Sv	to	342·10 ⁻⁷ Sv				2.2 %		
		342·10 ⁻⁷ Sv	to	137·10 ⁻⁵ Sv				2.5 %		
Photon dose equivalent rate (p Hx) / Meters of ionizing radiation dosimetry quantities		137·10 ⁻⁵ Sv	to	342 Sv				2.2 %	Measurement on the OG-8 irradiator	VF 1Q-3P2-0101
		342·10 ⁻⁹ Sv·h ⁻¹	to	137·10 ⁻⁷ Sv·h ⁻¹			4	2.2 %		
							5	3.9 %	Measurement on the OG-8 irradiator	VF 1Q-3P2-0101
		137·10 ⁻⁷ Sv·h ⁻¹	to	810·10 ⁻⁷ Sv·h ⁻¹			7	4.9 %		
							4	2.2 %		

Accredited entity according to ČSN EN ISO/IEC 17025:2018:

VF, a.s.
CAB number 2336, VF Calibration Laboratory
Svitavská 588, 679 21, Černá Hora

Ord. number ¹	Calibrated quantity / Subject of calibration	Nominal range				Parameter(s) of the measurand	Lowest stated expanded measurement uncertainty ²	Calibration principle	Calibration procedure identification ³	Work-place
		min.	unit	max.	unit					
2*		810·10 ⁻⁷	Sv·h ⁻¹	to	171·10 ⁻⁵	Sv·h ⁻¹	5 1 4	3.9 % 2.5 % 2.2 %		
		171·10 ⁻⁵	Sv·h ⁻¹	to	331·10 ⁻⁴	Sv·h ⁻¹	1 3	2.5 % 2.2 %		
		331·10 ⁻⁴	Sv·h ⁻¹	to	111·10 ⁻²	Sv·h ⁻¹	2 3	2.2 % 2.2 %		
		111·10 ⁻²	Sv·h ⁻¹	to	10.3	Sv·h ⁻¹	2	2.2 %		
		7·10 ⁻¹	Bq·cm ⁻²	to	2.5·10 ³	Bq·cm ⁻²		1.4 %	Measurements using planar sources of ionizing radiation	VF 1Q-3P2-0102
2*	Surface activity of alpha radionuclides (As) /Meters of contamination	20	Bq	to	2·10 ⁵	Bq		1.4 %	Measurements using planar sources of ionizing radiation	VF 1Q-3P2-0102
	Activity of alpha radionuclides (A) / Meters of contamination	2.5·10 ⁻¹	Bq·cm ⁻²	to	2.5·10 ⁶	Bq·cm ⁻²		1.4 %	Measurements using planar sources of ionizing radiation	VF 1Q-3P2-0102
	Surface activity of beta radionuclides (As) /Meters of contamination	4·10 ¹	Bq	to	2·10 ⁶	Bq		1.4 %	Measurements using planar sources of ionizing radiation	VF 1Q-3P2-0102
	Activity of beta radionuclides (A) / Meters of contamination	8·10 ⁻²	Gy	to	2.5·10 ³	Gy		5.4 %	Measurements using planar sources of ionizing radiation	VF 1Q-3P2-0103
3*	Kerma in air (Ka) /Meters of ionizing radiation dosimetry quantities	5	Gy·h ⁻¹	to	2.5·10 ³	Gy·h ⁻¹		5.4 %	Measurement using a comparator	VF 1Q-3P2-0103
	Kerma rate in air (p Ka) / Meters of ionizing radiation dosimetry quantities	5	Gy·h ⁻¹	to	2.5·10 ³	Gy·h ⁻¹		5.4 %	Measurement using a comparator	VF 1Q-3P2-0103

**The Appendix is an integral part of
Certificate of Accreditation No. 516/2023 of 02/10/2023**

Accredited entity according to ČSN EN ISO/IEC 17025:2018:

VF, a.s.
CAB number 2336, VF Calibration Laboratory
Svitavská 588, 679 21, Černá Hora

- ¹ Asterisk at the ordinal number identifies the calibrations, which the Laboratory is qualified to carry out outside the permanent laboratory premises.
- ² The expanded measurement uncertainty is in accordance with ILAC-P14 and EA-4/02 M a part of CMC and it is the lowest value of the respective uncertainty. If not stated otherwise, its coverage probability is approx. 95 %. If not stated otherwise, the uncertainty values stated without a unit are relative to the measured value. The uncertainty value stated herein is based on the best conditions achievable by the laboratory; the uncertainty value of a specific calibration may be higher depending on the conditions of such a calibration. For identical extreme values of adjacent ranges, the lower uncertainty value always applies.
- ³ If the document identifying the calibration procedure is dated, only these specific procedures are used. If the document identifying the calibration procedure is not dated, the latest edition of the specified procedure is used (including any changes).
- ⁴ OG-8 is a gamma irradiator, the number indicates the sealed radionuclide source in the irradiator